Product Code
00-A200-05-M1

Installation Instructions
3D File
Photometry
Revit (BIM)

Configurator

Tubs Modular Track with 3 Ceilings


Nahtrang Studio


Pendant Tubs Modular Track with 3 Ceilings LED 16W 2700K ON-OFF Black 184lm

Technical features

Luminaire total power: 16W
Real lumens: 202
Real lm/W: 13
Correlated Colour Temperature (CCT): 2700K
Structure material: Aluminium
Structure finish: Black
Diffuser material: Methacrylate
Diffuser finish: Opal
Driver Brand: INVENTRONICS
Voltage / frequency: 220-240V/50-60Hz
Dimming protocol: ON-OFF
Power Factor: NULL
Useful life: 50,000h L80B20
Warranty: 5 years
Easily recyclable luminaire

IP20 | 360° | LED | DRIVER | D (A↑G) | 87x244





Luminotechnic features

CRI: 92
MacAdam steps: 3
Photobiological risk: RG0

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	14.4W	2700K

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.

ledsc4@ledsc4.com
LedsC4, Afores s/n 25750 Torà (Lleida) Spain +34 973 468 100

Tubs Modular Track with 3 Ceilings

Nahtrang Studio

Pendant Tubs Modular Track with 3 Ceilings LED 16W 2700K ON-OFF Black 184lm

Logistics

x 1

Net weight (kg): 3.73
Packaged weight (kg): 6.69
Packaging: 1650mm x 175mm x 264mm

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.